



KETTLITZ-Antitack BTO-7

- Technical leaflet -

Antitack BTO-7 is a pigment-free antitack agent for the treatment of unvulcanized rubber compounds based on different bio-degradable detergents in combination with anti-foam and anti-corrosive additives.

The product was developed especially for treatment in batch-off equipment working in dipping or spraying system. The use of Antitack BTO-7 results in an extremely proper production site and in a very low wear and tear of machinery.

Another application is the treatment of profiles, bellows, bushings or similar products to avoid that the vulcanized products may stick together or to make the assembly of these parts easier.

After drying the use of Antitack BTO-7 results in a transparent film which can be washed off easily.

The concentration of the antitack agent can be determined by conductivity, i. e. an automatic dosage is possible. More information on this matter can be given upon request.

Recommended dosage for first trials: 1:15 (Antitack BTO-7:H₂O).

Antitack BTO-7 is of relatively low viscosity and can be diluted even with cold water in every dilution rate without problems.

Physical Properties

Chemical Characteristics

Combination of different biologically degradable detergents with antirust and antifoam agents

Appearance

Yellow, slightly opaque liquid

Density at 15 °C

(g/cm³)

1.030 ± 0.010

Dry Matter (0.5 g/15 min./109 °C)

(%)

21.0 ± 2.5

pH-Value at 20 °C (diluted 1 + 10)

7.0 ± 1.0

Physiol. Behavior

see safety datasheet

Storage Stability

2 years at room temperature in original sealed drums

Packing

plastic drums containing 100 kg net

Please visit our website, www.kettlitz.com, for full product list catalogue, or contact our exclusive agency in Iran: Iran Industrial Rubber co.

Tel: +98 21 2267 0733
+98 21 2267 0832
Fax: +98 21 2220 9247