IIR CO.

IIRCO HSi_®066 دورانیت



Product's Specification:

INDEX N	NAME	INDEX VALUE
PHYSICAL PERFORMANCE	Appearance	Ivory-White granule
	Tensile Strength	≥10.0 MPa
	Schopper Hardness (A)	≥93
	Mooney Viscosity ML 100°C	45-60
CHEMICAL PERFORMANCE	Volatiles	<i>≤</i> 5%
	Organic Acid	3.5~5.5%
	Soap Content	≤0.5%
	Styrene Content	66-70%

Properties: IIRCO HSi®066 is a non-polar polymer prepared from the co-polymerization of styrene and butadiene latex. It is white granule, non-toxic, odorless and combustible. Heat distortion temperature: 70-90°C, white solid. It is used as filling reinforcing agent to improve the hardness, aging-resistance, wear-resistance, tear strength and tensile strength of rubbers. Has excellent thermo plasticity and electrical insulating property.

Application: IIRCO HSi®066 is suitable for the manufacture of high-hardness and low-density products. 1. Shoe-making: hard soles, heel, rigid foam sole, imitation leather shoes etc.; 2. As floor materials: rubber floor tile; industrial products, like rubber roll, washer, hard rubber tube and other sponge products; 3. Sports industry: balls, roller-skate; 4. Electrical insulating material; 5. High-grade bike cover tire; various printing pastern roller; slab rubber; 6. ABS, AS plastic;

Package: 20.00±0.2kgs/bag, Kraft paper bag.

Storage: Protect against fire, water and sunlight. Stored in cool and draughty place. Shelf life: 1 year.

<u>IIRCO.</u>		ں ھاشمی	بازرگانی هاشمی	
Tel:	021-22670733	. 7 1_7 7 7 4 . 4 4 4	تلفن:	
Fax:	021-22670832 021-22209247	• 41_4494 • M44 • 41_449 • M44	فاكس	
	IIRCO.TRADING@YAHOO.COM	IIRCO.TRADING@YAHOO.COM		

IIRCO MADE IN CHINA, FOR INDUSTRIAL USE ONLY